



## TC2

## TRUCK CLEANER PERLOBAN®

### ■ Properties

- New bi-polar formula, thanks to an exclusive composition: PERLOBAN®.
- Especially conceived for the exterior washing of buses and trucks.
- Two very distinct functions: cleaning and auto-dry, this last having the advantage to increase finish «brilliance without stains» without having to dry the vehicle.
- The solution to the problems of stains on the big vertical surfaces of the buses.
- Removes easily the dirt so-called static (road film).
- Of multiple uses, it is especially recommended as a prewash product by pulverization because of its soaking strength.
- Usable in chemical bows, portal carwashes, high pressure devices, foam canons, pulverization and hand-washing.

### ■ Directions for use

**Pulverization:** Mix a dilution with water between 2 and 5%. Pulverize the vehicle from bottom to top and let act about 2 minutes. Then rinse with high pressure. For very dirty vehicles, you can mix dilutions with water up to 10% and then use it as previously described.

**Foaming unit:** Usable in all foaming devices. Dosage varies according to the device (consult our technical service).

**High-pressure:** Dosage at the nozzle exit must vary from 0,5% to 2%. Can be used with cold water, but we recommend a temperature between 40 and 50°C, this will increase the washing quality.

**Portal carwash:** To regulate the dosage pump please consult our technical service.

In any case, rinse always with clear water.

**For more detailed information please consult our technical support.**

### ■ Precautions for use

Respect the usual precautionary measures for handling chemicals: wearing gloves, goggles and protective clothing. Avoid contact with skin and eyes. Avoid all unnecessary exposure.

**For more detailed information please consult the safety material data sheet of this product.**

### ■ Technical specifications

**Physical state:** light brown liquid

**pH:** ca.13,5 - **Density:** ca.1,09

**Biodegradability environment:** The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents.

**Storage: keep tightly closed and protected from cold, frost, UV rays and heat in a ventilated place.**

### ■ References and packaging

TC2-27 Can 27 kg  
TC2-220 Barrel 220 kg

The packaging can be reused or recycled after cleaning.



We disclaim all responsibility for handling, storage, use or disposal of the product which would differ from the recommendations advocated by FLOWEY®.